

4T Marine Outboard 10W40

Product Data Sheet | Art.no 4A14.04

Description

This modern universal four-stroke engine oil is extremely suitable for high-revving and heavy-duty outboard motors. Meets the latest requirements for outboard motors as laid down by the NMMA. This oil is not suitable for passenger cars; for these, other requirements are set.



Available in



1L



5L



20L



60L



208L

Typical standard analyses

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	6230
Viscosity 40 °C, mm ² /s	89,40
Viscosity 100 °C, mm ² /s	13,40
Viscosity Index	151
Flash Point COC, °C	218
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,7

Performance level

NMMA FC-W

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms