

4T Motorcycle HS 10W40

Product Data Sheet | Art.no 4A12.01

Description

Semi-synthetic motorcycle oil. Based on high quality, mineral and synthetic oil. Specially developed for modern motorcycles. Using this oil slippage, sticking and difficulty shifting the clutch plates are things of the past.



Available in



1L



5L



20L



60L



208L

Typical standard analyses

Density at 15 °C, g/ml	0.876
Kinematic viscosity at 40 °C, mm ² /s	91
Kinematic viscosity at 100 °C, mm ² /s	14.1
Viscosity index	160
B.N. (HClO ₄ method), mg KOH/g	6.6
Pour point, °C	-39
CCS viscosity at -25 °C, mPa.s	5600
Flash Point COC, °C	224

Performance level

API SL
JASO MA/MA2

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms