

Coolant Universal -36

Product Data Sheet | Art.no 24.092HD

Description

Long Life coolant that offers exceptional protection against corrosion, particularly for aluminium and ferroalloys. Is nitrite, amine, borate, phosphate, nitrate and silicate-free. Universal coolant, mixable with all types. Can replace practically all types of coolant. Use undiluted, NEVER top up with water.



Available in



1L



5L



25L



60L



200L



1000L



Bulk

Typical standard analyses

Specific gravity at 20 °C, kg/l	1.068
Water contents Wt%	max. 53
pH-value	8,5
Freezing point (ASTM D 1177)	-36
Reserve alkalinity	5
Colour	Light yellow

Performance level

Mercedes-Benz/Daimler Chrysler MB 325.0, MB 325.2 en MB 325.3
Volkswagen TL-VW 774 D (G12) , TL-VW 774 F (G12+)
Cummins
DAF 74002
Deutz-MWM
Detroit Diesel (incl. Powercool plus) en 0199-99-1115 / 0199-99-2091
Ford WSS-M97B44-D
Landrover
Aston Martin
Jaguar
General Motors B0401065 en Saab/Opel GM6277M
Mazda
MG-Rover
PSA
Mitsubishi
Suzuki
Yanmar
Daewoo
Nissan

Coolant Universal -36

Product Data Sheet | Art.no 24.092HD

MAN 324 Typ SNF
Volvo Trucks
Renault Type D
Scania TB1451
Fiat 9,55523
Iveco standard 18-1830
BS 6580, BR-637, SAE J1034
ASTM D3306/D4656/D4985
JASO M325
NATO S-759
JIS K2234
Fendt
John Deere JDMH5
Behr
Jenbacher
ADE
MAK
MTU MTL 5048
Isuzu
Komatsu
Karosa
Leyland-DAF
Wärtsilä
Liebherr
JIS K2234 Class 2 (LLC)

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms