

Hybrid 0W20

Product Data Sheet | Art.no 4A06.53

Description

Fuel-saving, specially composed engine oil. Suitable for petrol and diesel engines, with or without turbo charger, in passenger vehicles and delivery vans. Also exceptionally suitable for hybrid and various other eco models.



Available in



1L



5L



20L



60L



208L

Typical standard analyses

Density at 15 °C, kg/l	0,846
Viscosity -35 °C, mPa.s	5320
Viscosity 40 °C, mm ² /s	46,70
Viscosity 100 °C, mm ² /s	8,54
Viscosity Index	162
Flash Point COC, °C	230
Pour Point, °C	-48
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	1,22

Performance level

ACEA A1/B1
API SH/CF

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms