

Hydrotrac HS

Product Data Sheet | Art.no 4Y05.1

Description

Semi-synthetic oil specially for lubricating hydrostatic drives for, amongst other things, riding mowers, garden tractors and so-called zero-turn mowers. Ensures problem-free propulsion, even in cold weather.



Available in



1L



5L

Typical standard analyses

Density at 15 °C, kg/l	0,873
Viscosity -25 °C, mPa.s	6470
Viscosity 40 °C, mm ² /s	95,40
Viscosity 100 °C, mm ² /s	14,20
Viscosity Index	153
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,29

Performance level

ACEA A3/B4-12
API SL/CF

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms