

# Hypersynth 5W40

Product Data Sheet | Art.no 4A0620

## Description

Synthetic, fuel-saving, universal, top quality engine oil. Designed for petrol and diesel engines requiring the most modern specifications. Ideal for direct-injection turbo diesel engines.



## Available in



1L



5L



20L



60L



208L



1000L



Bulk

## Typical standard analyses

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5740
Viscosity 40 °C, mm <sup>2</sup> /s	90,20
Viscosity 100 °C, mm <sup>2</sup> /s	15,00
Viscosity Index	173
Flash Point COC, °C	223
Pour Point, °C	-42
Total Base Number, mgKOH/g	10,5
Sulphate Ash, %	1,33

## Performance level

ACEA A3/B4-12
API SN/CF
VW 502.00/505.00
MB 229.3/226.5
Porsche A40
BMW Longlife-01
GM LL-B-025
Renault RN0700/RN0710
Fiat 9.55535-M2

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)