

# Lawn Mower 10W30

Product Data Sheet | Art.no 4A04.01

## Description

Engine oil for all petrol and diesel engines of lawn mowers and small machinery. Usable in all seasons. Provides optimal engine protection in the most taxing conditions. Makes for a rapid cold start and is resistant to high temperatures. Keeps engines clean and prevents deposits.



## Available in



0,6L



1L



5L



20L



60L



208L

## Typical standard analyses

Density at 15 °C, g/ml	0.872
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	78.3
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	11.9
Viscosity index	147
Flash Point COC, °C	220
Pour point, °C	-33
B.N. (HClO <sub>4</sub> method), mg KOH/g	10.1

## Performance level

ACEA A3/B3  
ACEA A3/B4  
API SN/CF

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E [info@gvg.nl](mailto:info@gvg.nl) - [www.gvg.nl](http://www.gvg.nl)

**AGEALUBE**<sup>®</sup>  
OIL FOR PROFESSIONALS