

Lawn Mower 30

Product Data Sheet | Art.no 4A03.03

Description

A high-quality engine oil for all intensively used four-stroke engines of lawn mowers, generators and other auxiliary motors. Provides a stable, lubricating film even at high temperatures. Keeps engines cleaner and prevents wear.



Available in



0,6L



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,886
Viscosity 40 °C, mm ² /s	97,40
Viscosity 100 °C, mm ² /s	10,80
Viscosity Index	107
Flash Point COC, °C	230
Pour Point, °C	-25
Total Base Number, mgKOH/g	7,1
Sulphate Ash, %	0,91

Performance level

ACEA E2
API SG/CF

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE
OIL FOR PROFESSIONALS