

Motorcycle FS 15W50

Product Data Sheet | Art.no 4A1205

Description

Fully-synthetic motorcycle oil, based on high-quality synthetic oil. Specially developed for modern, very heavy-duty motorcycles. With this oil, slippage, sticking and difficulty in shifting the clutch plates are things of the past.



Available in



1L



5L



20L

Typical standard analyses

Density at 15 °C, kg/l	0,845
Viscosity -20 °C, mPa.s	4000
Viscosity 40 °C, mm ² /s	111,30
Viscosity 100 °C, mm ² /s	17,10
Viscosity Index	168
Flash Point COC, °C	218
Pour Point, °C	-44
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,94

Performance level

API SL
JASO MA2
JASO MA

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms