

Multi Trac 10W40

Product Data Sheet | Art.no 4A112

Description

Multifunctional STOU oil for agricultural and earth-moving equipment, specially developed to lubricate petrol and diesel engines, transmissions (also oil-cooled hydraulic brakes) and the hydraulic system.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	4850
Viscosity 40 °C, mm ² /s	88,40
Viscosity 100 °C, mm ² /s	14,70
Viscosity Index	156
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,55

Performance level

API SF/CG-4/GL-4
ACEA E3
Mil-L-2104D
Massey Ferguson M1144/M1145
MB 227.1
ZF TE-ML 06B/07B
Ford M2C134-D
Massey Ferguson CMS M1143
John Deere J20C
CAT TO-2
Allison C4

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms