

Prolong LSP 5W30

Product Data Sheet | Art.no 4A06.45

Description

Fuel-saving, full-synthetic engine oil. Suitable for petrol, LPG and diesel engines of passenger cars and delivery vans, with or without turbo, for which extended oil change intervals are possible. Very low SAPS content, and therefore a longer service life of soot filters and catalytic converter. Suitable for MB 229.51/BMW LL 04.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5470
Viscosity 40 °C, mm ² /s	69,50
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	174
Flash Point COC, °C	210
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,3
Sulphate Ash, %	0,75

Performance level

ACEA C3-12
API SN
BMW Longlife-04
MB 229.31/229.51
Dexos 2
Opel OV 040 1547 - D30 / G30

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms