

Remvloeistof DOT 4

Product Data Sheet | Art.no 4A25

Description

Synthetic brake fluid with a low solidification point and good heat stability. Can be used in all braking systems in which DOT 4 is prescribed.



Available in



0,5L



1L



5L



20L



60L

Typical standard analyses

Kinematic viscosity at 100 °C, mm ² /s	2.1
pH	8.5
Equilibrium Reflux Boiling Point (ERBP), °C	263
Wet Equilibrium Reflux Boiling Point (WERBP), °C	165
Density at 20 °C, g/ml	1.040
Kinematic viscosity at -40 °C, mm ² /s	1400

Performance level

FMVSS 116 DOT 3/4
ISO 4925-3&4
SAE J1703/J1704

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms