

Schroefasvet

Product Data Sheet | Art.no 24.107

Description

Excellent water resistant lubricant. High pumpability and widely applicable. Propeller shaft lubricant for all stern tubes. Can also be used for all bearings on board and is suitable for general lubrication.



Available in



400g



1kg



5kg



18kg

Typical standard analyses

Colour	Brown
Soap Type	Calcium
Base oil type	Mineral Oil
Penetration at 25 °C	225-255
Copper corrosion	1a
Water resistance	Non soluble
Temperature range	-10°C tot 90°C

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE[®]
OIL FOR PROFESSIONALS