

Syn Gear UTTO

Product Data Sheet | Art.no 4A23.07

Description

Synthetic, very high quality, universal transmission oil for the most common agricultural and road construction machines (UTTO). Developed for the most heavy duty hydraulic and transmission systems, both with and without wet brakes.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,857
Viscosity 40 °C, mm ² /s	40.80
Viscosity 100 °C, mm ² /s	7,70
Viscosity Index	161
Pour point, °C	-48
TBN, mg KOH/g	7.4

Performance level

API GL-4
AGCO/ALLIS: 821 XL
Volvo WB 102
Case MS 1207 / MS 1209
DIN 51524-3 HVLDP
John Deere J20 D
KUBOTA: UDT²
MF M 1143
MF M 1145
ZF TE-ML 03E/05F/06K/17E/21F

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE
OIL FOR PROFESSIONALS