

Two Stroke Ashless Outboard

Product Data Sheet | Art.no 4A14

Description

Very high-quality two-stroke engine oil to which ashless two-stroke additives have been added, in order to guarantee good lubrication and also to prevent excessive carbon deposits and smoke formation. Can be used for all two-stroke outboard motors, with a mixing ratio of 1 to 50.



Available in



1L



5L



20L



60L



208L

Typical standard analyses

Density at 15 °C, kg/l	0,870
Viscosity 40 °C, mm ² /s	35,60
Viscosity 100 °C, mm ² /s	6,29
Viscosity Index	126
Flash Point PM, °C	107
Pour Point, °C	-30
Total Base Number, mgKOH/g	8,7

Performance level

NMMA TC-W3

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE[®]
OIL FOR PROFESSIONALS