

Vaseline Spray

Product Data Sheet | Art.no 26.016

Description

Transparent, universal lubricant and protective agent that adheres well. It does not attack rubber or seals, and is water-repellent and pH neutral (acid-free). It is resistant to weather and strong acids and alkalis. Has excellent corrosion-resistant properties and prevents wear and sticking. Can withstand temperatures between -30°C and 160°C . Uses: Battery terminals, AV equipment operating panels, fastening materials (e.g. screws, bolts, nuts, and nails), antennas and electrical contacts, etc.



Available in



400ml

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEA LUBE
OIL FOR PROFESSIONALS